

XT2000+ Primer

MATERIAL SAFETY DATA SHEET

SECTION I – PRODUCT IDENTIFICATION

Formulated Solutions LLC
25-44 Borough Place, Woodside, NY 11377
Telephone: 718-267-6380
Emergency Phone: 718-267-6380
Generic ID: Latex-based sealer for gypsum wallboard
Product Identity: XT2000+ Primer
Date Prepared: 1/1/11
Shipping Class: 55

SECTION II – INGREDIENTS

Ingredient Name	CAS Number	Percent	Exposure Limits
Water	7732-18-5	73–75	N/A
Latex Polymer	N/A	35–38	5000 ppm (TLV)

*Other Non-Hazardous Ingredients considered a Trade Secret

SECTION III – PHYSICAL DATA

Initial Boiling Point: 212°F
Vapor Pressure: Same as water
Vapor Density (Air=1.0): Same as water
Specific Gravity: 1.03–1.04
Percent Volatiles: 60–62.0%
VOC g/l: 0

SECTION IV – FIRE AND EXPLOSION DATA

Flash Point: N/A
Explosive Limit (Product): N/A
Extinguishing Media: None to avoid
SPECIAL FIRE FIGHTING PROCEDURES: None
UNUSUAL FIRE & EXPLOSION HAZARDS: None

SECTION V – HEALTH HAZARD DATA

Permissible Exposure Level: N/A
Threshold Limit Value: N/A

EFFECTS OF EXPOSURE

Skin: Possible mild irritation
Eyes: Possible mild irritation
Inhalation: None known

FIRST AID

Skin: Wash exposed skin with soap and water.
Eyes: Flush with water, lifting upper and lower lids occasionally
Inhalation: If affected, remove individual to fresh air. Use only in well-ventilated areas.
Ingestion: Do not induce vomiting. Call physician or transport to an emergency facility.

SECTION VI – REACTIVITY DATA

Stability: Stable
Incompatibility: None
Hazardous Decomposition: None
Hazardous Polymerization: None
Conditions to Avoid: None known

SECTION VII – SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED
OR SPILLED: Absorb liquid on paper, vermiculite, floor absorbent, or other absorbent material. Solidified materials accepted for landfill disposal in most locations.
Check all local, state, and federal regulations.

SECTION VIII – PROTECTIVE EQUIPMENT

Ventilation: Open all available windows and entrances to insure good ventilation.
Respirator Protection: None needed
Protective Gloves: If sensitive
Eye Protection: Wear glasses or protective goggles to avoid splashes.
Other Protective Equipment: None required
WASH HANDS THOROUGHLY WITH SOAP AND WATER.

SECTION IX – SPECIAL PRECAUTIONS

Protect from freezing.
Use only in applications as stated on the label. Do not take internally. Close container after each use. Avoid skin and eye contact.
Ventilation with fresh air, including open doors and windows should be observed during any installation. Operate HVAC systems at 100% fresh air intake before, during and after installation to eliminate lingering odors or particulate matter.

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the material if reasonable safety procedures are not followed as stipulated in this data sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the material.

KEEP OUT OF REACH OF CHILDREN